PATENT SPECIFICATION

1 535 826(11)

(21) Application No. 6752/76

(22) Filed 20 Feb. 1976

(31) Convention Application No. 2507461

(32) Filed 21 Feb. 1975 in

(33) Federal Republic of Germany (DE)

(44) Complete Specification published 13 Dec. 1978

(51) INT CL² C07C 47/19//31/18 47/20

(52) Index at acceptance

5

10

25

30

35

40

C2C 200 20Y 248 30Y 350 360 361 36Y 382 43X 507 509 50Y 54X 569 633 643 65Y 66Y TH TJ YP



5

10

15

20

25

30

35


(54) MANUFACTURE OF α,α -DIMETHYLOL-SUBSTITUTED ALIPHATIC ALDEHYDES

We, BASF AKTIENGESELLSCHAFT, a German Joint Stock Company of 6700 Ludwigshafen, Federal Republic of Germany, do hereby declare the invention, for which we pray that a patent may be granted to us and the method by which it is to be performed, to be particularly described in and by the following

The present invention relates to a process for the manufacture of aca-dimethylolsubstituted aliphatic aldehydes by reaction of an aldehyde with formaldehyde in the presence of a base.

German Printed Application 1,154,080 discloses the reaction of aldehydes, containing at least 3 carbon atoms and containing 2 hydrogen atoms in the α -position, with formaldehyde in the presence of basic compounds, e.g. alkali metal hydroxides or alkaline earth metal hydroxides, to give trimethylolalkanes. The reaction can be

represented by the following equation:



In this reaction, dimethylolaldehydes are formed as transient intermediates, which 15 react with formaldehyde and the base, in a Cannizzaro reaction, to give trimethylol compounds and a formate. The disadvantage of this process is that at least stoichiometric amounts of formates are formed as by-products. Because of the fact that they cause decomposition, the salts must be removed completely before the trimethylol compounds are purified by distillation, and these salts are a serious environmental 20 problem, particularly in large-scale production. It is not possible to manufacture pure dimethylolaldehydes satisfactorily by this method, since substantial amounts of formaldehyde undergo a Cannizzaro reaction with the alkanal in the presence of the basic

catalyst, and mixtures of components which are difficult to separate are formed.

German Published Application 1,952,738 discloses the use of lower tertiary organic amines as catalysts for the reaction of n-butyraldehyde with formaldehyde. In the examples, the use of trimethylamine and triethylamine is illustrated. In the description, only these two compounds are mentioned individually; from the statements made (page 3, 1st paragraph) it is merely possible to assume that straight chain trialkylamines, preferably with identical alkyl radicals, can be used. In this process, again, the formation of formates is neither avoided nor reduced. The advantage that the salt is more easily removable is counter-balanced by the increased effort required to regenerate the base. The process is unsatisfactory in respect of yield and purity of

the products.

U.S. Patent 3,077,500 discloses the reaction of aldehydes in the presence of tertiary amines and a basic anion exchanger, to give corresponding aldols; the patent teaches that, as a rule, the amine serves to maintain the catalytic activity of the exchanger resin. In the absence of the exchanger, the catalytic action of the amine alone is less; the conjoint use of the amine and the exchanger is emphasized particularly for the case of reactions carried out at atmospheric pressure. The process can also be carried out in the absence of the amine. All the amines mentioned in the description are straight-chain amines and the examples only illustrate the use of

40

5

10

15

5

10

15

20

25

30

trimethylamine and triethylamine. The examples further show that amines without the exchanger are only used in the case of the auto-condensation of a single aldehyde or of the condensation of formaldehyde with a ketone. Thus, e.g., the patent teaches that triethylamine brings about the auto-condensation of butyraldehyde (Example 9). Examples 10 and 11 show that with formaldehyde only one methylol group is condensed onto acetone or onto methyl ethyl ketone in the presence of triethylamine and in the absence of exchangers, even though there are other hydrogen atoms in the aposition to the carbonyl group and therefore further condensation would be possible.

position to the carbonyl group and therefore further condensation would be possible. In the reaction of aldehydes, containing 2 hydrogen atoms in the α -position, with formaldehyde, equilibria exist between the possible aldol-forming reactions and side reactions, e.g. elimination of water in the α - β -positions; in addition to the end products, a range of other products, in some cases of higher molecular weight, e.g. aldols and ether aldehydes, are formed. Hydrogenation of the reaction mixture gives trimethylol compounds contained in heterogeneous mixtures, from which they are difficult to isolate.

We have found that an advantageous method of obtaining an exa-dimethylolsubstituted aliphatic aldehyde of the formula

where R¹ is an aliphatic radical, by reaction of an aldehyde with formaldehyde in the presence of a base, is to react an aldehyde of the formula

where R¹ has the above meaning, with formaldehyde in the presence of a tertiary amine catalyst of the formula

where R² and R³ separately are identical or different aliphatic radicals, or together form with the linking nitrogen atom a heterocyclic ring and R⁴ and R⁵ are identical or different aliphatic radicals, and in addition R⁴ may denote hydrogen if (a) R⁵ denotes

$$R^{\mathfrak{o}}$$
 $R^{\mathfrak{o}}$ $R^{\mathfrak{o}}$ or (b) $R^{\mathfrak{o}}$ denotes $R^{\mathfrak{o}}$ $R^{\mathfrak{o}}$

and R²+R³+the linking N atom form a heterocyclic ring or (c) R⁵ denotes

and R2 denotes

15

20

25

30

35

5

20

45

and (ii) R⁵ may denote hydrogen if (a) R²+R³+ the linking N atom form a heterocyclic ring and R4 denotes an aliphatic radical or (b) R4 denotes an aliphatic radical and R2 denotes

Ro throughout denoting an aliphatic radical and individual radicals Ro and individual radicals R4 being identical or different.

When n-butyraldehyde is used, the reaction can be represented by the following

$$CH_2OH$$
 CH_3 — CH_2 — CH_2 — CH_2 — CH_3 — CH_4 — CH_2 — CH_5

10 Compared to the conventional process, the process according to the invention is able to give and-dimethylol-substituted aliphatic aldehydes more economically and more simply, in most cases in better yield, and in higher purity. In view of the purification operations required in the conventional processes the process of the invention generally gives a higher space-time yield of the overall operation, particularly on an industrial scale. The formation of by-products is substantially reduced and mixtures 15 containing by-products which are difficult to remove are not formed to a substantial degree. By-products formed are small amounts of the corresponding a-substituted acrolein and a-substituted alkenal as well as trimethylol-substituted aliphatic compound and N,N,N-trisubstituted ammonium formates.

Surprisingly, the formation of a-substituted acroleins is reversible under the conditions according to the invention; reaction of the acrolein with water and formaldehyde in the presence of the amine III gives α,α -dimethylol-substituted aliphatic aldehyde via α -monomethylol-substituted aliphatic aldehyde:

25 The a-substituted acroleins, which are the most important by-products formed, can thus be converted together with the dimethylol aldehydes, e.g. by hydrogenation, to industrially valuable a-substituted alkanols, or can be recycled to the synthesis of the dimethylol aldehyde. Trisubstituted ammonium formates can be isolated by distillation if their boiling point is sufficiently low, but when a trimethylol compound is to be produced, the said formates can, without disadvantage, be introduced into the 30 hydrogenation reactor together with the dimethylolaldehyde, and as a rule undergo an advantageous degradation, with liberation of the tert.-amine III. Thus, a further advantage of the process according to the invention compared to the conventional processes is that the by-products formed can be removed easily and can be converted 35 into industrially useful products. All these advantageous results are surprising in the light of the prior art. In the light of U.S. Patent 3,077,500, low yields, or at least poorer yields of end product, and the formation of heterogeneous mixtures containing aldols formed by auto-condensation of the aldehyde, and monomethylol compounds, would have been expected. It is especially surprising that particularly the branched alkylamines used according to the invention are exceptionally selective catalysts for 40 the reaction according to the invention.

The starting materials II are reacted with a stoichiometric amount or an excess of formaldehyde, preferably using a molar ratio of from 1 to 8 moles, and especially 2 to 4 moles, of formaldehyde per mole of starting material II. Preferred starting materials II and accordingly preferred end products I are those where R¹ is linear alkyl of 1 to 6 carbon atoms. The above alkyl radicals can further be substituted by groups which are inert under the reaction conditions, e.g. alkyl or alkoxy, each of 1

to 3 carbon atoms.

4	1,030,826	4
	Examples of suitable starting materials II are 3-ethyl-, 3-n-propyl-, 3-isopropyl-, 3-n-butyl-, 3-isobutyl, 3-secbutyl-, 3-tertbutyl-butanal and corresponding n-pentanals, n-hexanals and n-heptanals; 4-ethyl-, 4-n-propyl-, 4-isopropyl-, 4-n-	
5	butyl-, 4-isobutyl-, 4-secbutyl-, and 4-tertbutyl-pentanal, -n-hexanal and -n-heptanal; 5-ethyl-, 5-n-propyl-, 5-isopropyl-, 5-n-butyl-, 5-isobutyl-, 5-secbutyl- and 5-tertbutyl-n-hexanal and -n-heptanal; 3-methyl-hexanal and 3-methyl-heptanal; 4-methyl-pentanal, 4-methyl-heptanal, 5-methyl-hexanal and 5-methyl-heptanal; 3,3,5-	5
	trimethyl-n-pentyl-, 3,3-diethylpentyl-, 4,4-diethylpentyl-, 3,3-dimethyl-n-butyl-, 3,3-dimethyl-n-pentyl-, 5,5-dimethylheptyl-, 3,3-dimethylpentyl-, 3,3.4-trimethylpentyl-,	
10	3,4-dimethylheptyl-, 3,5-dimethylheptyl-, 4,4-dimethylheptyl-, 3,3-diethylhexyl-, 4,4-dimethylhexyl-, 4,5-dimethylhexyl-, 3,4-dimethylhexyl-, 3,5-dimethylhexyl-, 3,3-dimethylhexyl-, 3,4-diethylhexyl-, 3-methyl-4-ethylpentyl-, 3-methyl-4-ethylhexyl-, 3,4-trimethylpentyl-, 3,4,4-trimethyl-	10
15	hexyl- and 3,3,4,4-tetramethylpentyl- aldehyde; propanal, n-butanal, n-pentanal, 3-methylbutanal, n-hexanal, 3-methylpentanal, n-heptanal, 4-methyl-hexanal and n-octanal are preferred. The reaction is in general carried out at from 15 to 120°C, preferably fram 30 to	15
20	90°C and especially from 40 to 85°C, under reduced pressure, superatmospheric pressure or atmospheric pressure, preferably the latter, and batchwise or continuously. In general, water is used as the reaction medium, in most cases in the form of an aqueous formaldehyde solution, preferably containing from 20 to 40 percent by weight of formaldehyde. In total, the amount of water used can be from 20 to 80% by weight, advantageously from 40 to 60% by weight, based on total starting mixture.	20
25	alf desired, an organic solvent which is inert under the reaction conditions and preferably is readily miscible with water may also be present; advantageous solvents are cyclic ethers, e.g. tetrahydrofuran and dioxane, esters, e.g. methyl acetate, ethyl acetate and methyl propionate, and alkanols, e.g. ethanol, methanol, glycol, ethylene glycol monoethyl ether and methylglycol. Suitable amounts of solvent to use are from	25
30	50 to 1,000% by weight, preferably from 50 to 200% by weight, based on starting material II. Suitable amounts of catalyst III are from 0.03 to 0.15 mole, especially from 0.05	30
35	to 0.1 mole, per mole of starting material II. It is advantageous if the catalyst has a boiling point below that of the dimethylolalkanal II. Preferred tertiary amines are those defined above of the formula III where any aliphatic radical R ² , R ³ , R ⁴ , R ⁵ or R ⁶ is alkyl of 1 to 7 carbon atoms, more preferably of 1 to 5 carbon atoms in the case of R ² and R ³ and of 1 to 3 carbon atoms in the case of R ⁴ , R ⁵ and R ⁶ , optionally substituted by one or more dialkylamino groups and/or hydroxyl groups, preferably by one dialkylamino group or one hydroxyl group, preferably in the \(\omega-\text{position}, \text{ the alkyl}\)	35
40	groups of any dialkylamino groups being identical or different and each being of 1 to 5 carbon atoms, and where any heterocyclic ring formed by R ² and R ³ and the linking nitrogen atom has 5 or 6 ring members, which may include a further nitrogen	40
45	atom or an oxygen atom, and may further be substituted by one or more groups which are inert under the reaction conditions, e.g. alkyl or alkoxy groups each of 1 to 3 carbon atoms, dialkylamino groups each of 1 to 3 carbon atoms per alkyl, and hydroxyl groups.	45
	Examples of suitable catalysts III are N,N-di-(methyl)-, N,N-di-(ethyl)-, N,N-di-(n-propyl)-, N,N-di-(isopropyl)-, N,N-di-(n-butyl)-, N,N-di-(isobutyl)-, N,N-di-(secbutyl)-, N,N-di-(tertbutyl)-, N,N-di-(n-pentyl)-, N,N-di-(n-pentyl)-, N,N-di-(n-octyl)-, N,	
50	nonyl)-, N,N-di-(n-decyl)-, N,N-di-(2-ethylhexyl)-, N,N-di-(2,2,6-trimethyl-n-pentyl)-, N,N-di-(2-ethylpentyl)-, N,N-di-(2,3-dimethyl-n-butyl)-, N,N-di-(2,3-dimethyl-n-butyl)-, N,N-di-(2,2-dimethyl-n-butyl)-, N,N-di-(2-methylpentyl)-, N,N-di-(3-methylpentyl)-, N,N-di-(3-methylpentyl)-, N,N-di-(3-methylheptyl)-, N,N-di-(3-methylheptyl)-, N,N-di-(2,2-dimethylhexyl)-, N,N-di-(3-ethylhexyl)-, N,N-di-(2,2-dimethylhexyl)-, N,N-di-(3-methylhexyl)-, N,N-di-(3-methylhexyll)-, N,N-di-(3-methylhexyll)-, N,N-di-(3-methylhexyll)-, N,N-di-(3-methylhexyll)-, N,N-di-(3-methylhexyl	50
55	di-(2,3-dimethylhexyl)-, N,N-di-(2,4-dimethylhexyl)-, N,N-di-(2,5-dimethylhexyl)-, N,N-di-(3,3-dimethylhexyl)-, N,N-di-(3,4-dimethylhexyl)-, N,N-di-(2-methyl-3-ethylpentyl)-, N,N-di-(2,2,3-trimethylpentyl)-, N,N-di-(2,2,4-trimethylpentyl)-, N,N-di-(2,3,4-trimethylpentyl)-, N,N-di-(2,3,4-trimethylpentyl)-	55
60	pentyl)- and N,N-di-(2,2,3,3-tetramethylbutyl)-neopentylamine; corresponding amines with 2 of the above radicals which however differ from one another, e.g. N-methyl-N-ethyl-neopentylamine; 1,1-dimethyl-, 1,1-diethyl-, 1,1-di-n-propyl-, 1,1-diisopropyl-, 1,1-di-n-butyl-, 1,1-diisobutyl-, 1,1-di-secbutyl- and 1,1-di-tertbutylethylamines having substituents R ² and R ³ on the nitrogen atom corresponding to those on the	60
65	neopentyl-dialkylamines mentioned above; n-propylamines, isopropylamines, n-butyl- amines, isobutylamines, secbutylamines and tertbutylamines as far as possible cor-	65

5	1,535,826	
	respondingly substituted in the 1-position of the alkyl radical and also correspondingly disubstituted on the nitrogen atom; N-(1,1-dimethyl-ethyl)-, N-(1,1-diethyl-ethyl)-, N-(1,1-di-n-butyl-ethyl)-, N-(1,1-di-n-butyl-ethyl-ethyl)-, N-(1,1-di-n-butyl-ethyl-	
5	(1,1-diisobutyl-ethyl)-, N-(1,1-di-secbutyl-ethyl)- and N-(1,1-di-tertbutyl-ethyl)- pyrrolidines as well as N-n-propyl-, N-isopropyl-, N-n-butyl-, N-isobutyl-, N-sec	-5
,	buryl- and N-tert,-butyl-pyrrolidines as far as possible correspondingly substituted in	
	the 1-position of the alkyl radical; piperidines, N'-methylpiperazines and morpholines substituted analogously to the above pyrrolidines, and analogous piperazines substi-	
10	tuted at the 2nd nitrogen atom by the ethyl, n-propyl, isopropyl, n-butyl, isobutyl, sec butyl or tertbutyl group, N-neopentyl-pytrolidine, N-neopentyl-piperidine, N-neo-	10
10	pentyl-N'-methyl-piperazine, N-neopentyl-morpholine and analogous piperazine sub-	. 10
	stituted at the 2nd nitrogen atom by the ethyl, n-propyl, isopropyl, n-butyl, isobutyl, secbutyl or tertbutyl group; 2,2-diethyl-, 2,2-di-n-propyl-, 2,2-diisopropyl-, 2,2-di-	
1.6	n-butyl-, 2,2-diisobutyl-, 2,2-di-secbutyl- and 2,2-di-tertbutyl-n-propyl-dialkyl- amines and -heterocyclics corresponding to the above N-neopentyl-dialkylamines and	. 15
15	N-neopentyl-heterocyclics, as well as the analogously substituted 2,2-dimethyl-, 2,2-di-	. 13
	ethyl-, 2,2-n-propyl-, 2,2-diisopropyl-, 2,2-di-n-butyl-, 2,2-diisobutyl-, 2,2-di-secbutyl- and 2,2-di-tertbutyl-n-butyl compounds and -ethyl compounds, and n-butyl com-	٠.
20	pounds which are disubstituted by the methyl, ethyl, n-propyl, isopropyl, n-butyl, isobutyl, secbutyl or tertbutyl group both in the 2-position and in the 3-position;	20
20	isopropyl-pyrrolidine, secbutyl-pyrrolidine and analogously substituted piperidines,	20
	N'-methyl-piperazines, morpholines and piperazines which are analogously substituted at the 2nd nitrogen atom by the ethyl, n-propyl, isopropyl, n-butyl, isobutyl, secbutyl	
26	or tert-buryl group; monoalkylamines, substituted correspondingly to the above N-neopentyl-dialkylamines, which in place of the neopentyl group and an alkyl group	26
25	carry 2 isopropyl groups or 2 isobutyl groups or 2 isopropyl groups which are sub-	25
	stituted in the 1-position, or in the 1-position and at the same time in one or both of the ω -positions, by, in each case, 2 methyl, 2 ethyl, 2 n-propyl, 2 isopropyl, 2 n-butyl,	
20	2 isobutyl, 2 secbutyl or 2 tertbutyl groups, or 2 isobutyl groups which are substituted in one or both of the ω-positions by, in each case, 2 methyl, 2 ethyl, 2 n-	20
30	propyl, 2 isopropyl, 2 n-butyl, 2 isobutyl, 2 secbutyl or 2 tertbutyl groups; and	30
	corresponding tertiary amines which carry a hydroxyl group, or a dimethylamino, diethylamino, di-n-propylamino, diisopropylamino, di-n-butylamino, diisobutylamino,	•
25	di-secbutylamino or di-tertbutylamino group in the ω-position of 1 or 2 or all alkyl	25
35	groups. Preferred catalysts III are dimethylamino-neopentanol, 3-dimethylamino-2-methyl-2-propyl-propanol, 2,2-dimethyl-N,N'-tetramethyl-1,3-propylenediamine,	35
	pyrrolidino-neopentanol, 1-dimethylamino-neopentane, 1-dimethylamino-2,2-di- methylolpropane, 1-dimethylamino-2,2-dimethylolbutane, methyl-diisobutylamine,	
40	ethyl-diisopropylamine, propyl-diisopropylamine, triisopropylamine, triisobutylamine, propyl-diisobutylamine, n-butyl-diisobutylamine, N-isopropyl-pyrrolidine, N-isobutyl-	40
	pyrrolidine, N-isopropyl-piperidine, N-isobutyl-piperidine, methyl-ethylamino-neo- pentanol, diethylamino-neopentanol, piperidino-neopentanol, 3-(methyl-ethylamino)-2-	
45	methyl-2-propyl-propanol, 3-pyrrolidino-2-methyl-2-propyl-propanol, 3-piperidino-2-methyl-2-propyl-propanol, 3-dimethylamino-2-ethyl-2-butyl-propanol, 1-pyrrolidino-	45 ⁻
	2,2-dimethylolpropane, 1-(methyl-ethylamino)-2,2-dimethylolpropane, 1,3-bis-[dimethylamino]-2,2-dimethylpropanol, methylethylamino-neopentane, 1,3-bis-[dimethylamino]-2,2-dimethylpropanol, methylethylamino-neopentane, ethyl-diisobutylamine, butyl-diisopropylamine, tertbutyl-diiso-	
	propylamine, N-isopropyl-morpholine, N,N'-diisopropyl-piperazine, N-isobutyl-	
50	morpholine, N,N'-diisobutyl-piperazine, N-tertbutyl-pyrrolidine, N-tertbutyl- piperidine and N-tertbutyl-morpholine.	50
	The reaction can be carried out as follows: a mixture of starting material II, formaldehyde, water and catalyst, if appropriate together with solvent, is kept at the	
	reaction temperature for from 10 to 240 minutes, preferably from 15 to 60 minutes.	٠.
55	The end product is then isolated from the reaction mixture in the usual manner, for example by distillation. An advantageous method of batchwise operation is to intro-	55
	duce the catalyst into the mixture of the starting materials, whilst this mixture is stirred within the stated temperature range, at a rate such that the heat of reaction	
	can suitably be removed by cooling. It is also possible to take the aldehyde II and add	
60	formaldehyde and amine III conjointly thereto. For continuous operation, it is possible to use, e.g., a packed reaction tube or a stirred kettle cascade. The dimethylol-	60
	aldehyde product I can be isolated from the reaction product by stripping off any excess formaldehyde and distilling off the solvent, the catalyst and the lower-boiling	: .
	by-products, the dimethylol aldehyde being left as the residue; alternatively, the dimethylol aldehyde can be subjected to further conversion, e.g. hydrogenation, directly	
65	memyor anenyue can be subjected to rurated conversion, e.g. nyurogenation, uncerty	65

	-,5-5-,0-2-0	
	in the reaction mixture. The term "stripping" is used to denote purifying a material by removing another material in the form of a vapor mixture, e.g. the distillation vapor, in accordance with the definition in "Introduction to Chemical Engineering" by W. L. Badger and J. T. Banchero (McGraw-Hill Book Co. Inc. 1955), page 437, last	
5	paragraph. Surprisingly, dimethylolaldehydes I where R ¹ is alkyl of 1 to 4 carbon atoms, i.e. up to 2,2-dimethylolhexanal, in the form produced according to the invention, can be distilled substantially without decomposition, and purified, on thin film evaporators at below 200°C, under reduced pressure. Whilst in all conventional processes a similar distillation of the desired dimethylol aldehyde I leaves residues and	5
10	gives a distillate which is not a single substance, the end products I manufactured according to the invention as a rule leave less than 3% by weight of residues and thus give a purer dimethylol aldehyde. As may be seen from the Examples, the end products I manufactured in this way can be hydrogenated to trimethylol compounds R ¹ —C(CH ₂ OH) ₃ simply and in accordance with conventional methods.	. 10
15	The dimethylol aldehydes I which may be manufactured by the process of the invention are valuable intermediates for the manufacture of trimethylol compounds, e.g. 1-trimethylolethane and 1-trimethylolpropane, which are industrially important components of polyurethane resins, alkyd resins, drying oils and plasticizers. They are, furthermore, starting materials for dimethylolcarboxylic acids, e.g. dimethylolpropionic	15
20	acid and dimethylolbutyric acid, for dyes and for pesticides. Regarding their uses, reference may be made to the publications mentioned above and to Ullmanns Encyklopadie der technischen Chemie, Volume 3, pages 295 to 298. In the Examples, parts are by weight.	20
	EXAMPLE 1	
25	26 parts of dimethylaminoneopentanol are added in the course of 10 minutes to a mixture of 488 parts of 37 per cent strength by weight formaldehyde and 144 parts of n-butyraldehyde whilst stirring at from 20 to 70°C. The reaction mixture is then stirred for a further 20 minutes at 78°C under reflux. The formaldehyde content is	25
30	lowered to 0.05% by weight (based on the mixture) by stripping with steam, and the water and low-boiling constituents are removed by distillation, using a Sambay evaporator, at from 135 to 140°C and 10 mm Hg. 223 parts of crude dimethylobutanal, corresponding to a yield of 84.5% of theory, based on n-butyraldehyde employed, are left as the residue. Distillation at 170°C and 2 mm Hg gives 212 parts of pure end product (80.3% of theory) of boiling point 133°C at 1 mm Hg.	30
35	Continuous catalytic hydrogenation of the pure end product in tetrahydrofuran (25 percent strength solution) at 110°C and 250 bars pressure of H ₂ , over a fixed bed hydrogenation catalyst consisting of 68% by weight of CuO, 6.4% by weight of Mn ₃ O ₄ , 3.6% by weight of MoO ₃ and 3% by weight of H ₂ PO ₄ (3 mm diameter catalyst extrudates), and fractional distillation, gives 199 parts of trimethylolpropane	35
40	of boiling point 151°C at 1—2 mm Hg (melting point 53°C), corresponding to 92.4% of theory, based on pure end product, or 74.3% of theory, based on n-butyr-aldehyde employed.	40
45	By way of comparison with Example 1, 488 parts of 37 per cent strength by weight formaldehyde and 144 parts of n-butyraldehyde are reacted with the aid of catalysts K at temperatures T, using the processes shown in the Table. Working up analogously to Example 1 gives crude dimethylolbutanal (CD) in yields of $A_1\%$ of theory, or pure end product (DMB) in yields of $A_2\%$ of theory, based on n-butyraldehyde employed, in addition to R% of residue (based on CD). Hydrogenation	45
50	of the end product analogously to Example 1 gives A ₅ % of theory of trimethylol- propane (TMP), based on n-butanal.	50

			TABLE	三三			
Example	Ж	T°C	A, % CD	A, % DMB	R%	A, % TMP	Process
	Dimethylaminoneopentanol	75–80	84.5	80.3	1.6	74.3	74.3 Example 1
7	Triethylamine (20 parts)	75-80	85	19	18.8	57	analogously to Example 1
6	Triethylamine	80	79	63	20	51	U.S. Patent 3,077,500
							Example 9

EXAMPLE 4

34 parts of triisobutylamine are run into a mixture of 488 parts of 37 per cent strength by weight formaldehyde and 144 parts of n-butyraldehyde in the course of 10 minutes whilst stirring at from 20 to 70°C. The reaction mixture is then stirred for a further 40 minutes at 78°C under reflux. Distillation and hydrogenation analogously to Example 1 give 216 parts of crude dimethylolbutanal (81.8% of theory) or 207 parts of pure dimethylolbutanal (78.4% of theory) or 191 parts of trimethylolpropane, corresponding to 71% of theory, based on n-butyraldehyde.

EXAMPLE 5

130 parts of dimethylaminoneopentanol are run into a mixture of 1,625 parts of 37 percent strength by weight formaldehyde and 720 parts of n-butyraldehyde in the course of 15 minutes whilst stirring at from 20 to 80°C. The reaction mixture is then stirred for a further 30 minutes at from 80 to 83°C under reflux. The mixture is distilled using a Sambay evaporator, at 135°C and 10 mm Hg, giving a residue of 909 parts of crude dimethylolbutanal (68.9% of theory) and 1,350 parts of a two-phase distillate. The aqueous phase is brought to pH 8, organic constituents dissolved in the water are distilled off up to a bottom temperature of 100°C, under atmospheric pressure, and the distillate is combined with the organic phase. Fractional distillation of the mixture gives 195 parts of a fraction of boiling range 60—95°C, containing 40 parts of n-butyraldehyde (5.6% by weight, based on n-butyraldehyde). 190 parts of 37 per cent strength by weight formaldehyde and 25 parts of dimethylaminoneopentanol are added and the mixture is heated at from 60 to 82° for 5 hours, whilst stirring. After distilling off the low-boiling constituents at 135°C and 10 mm Hg, using a sambay evaporator, 226 parts of crude dimethylolbutanal are obtained as the residue. Total yield: 1,135 parts of dimethylolbutanal, corresponding to 85.5% of theory, based on n-butyraldehyde. Hydrogenation and fractional distillation according to Example 1 give 1,010 parts of trimethylolpropane of boiling point 150—152°C at 1—2 mm Hg (melting point 52°C), corresponding to 75.3% of theory, based on n-butyraldehyde.

EXAMPLE 6

26 parts of dimethylamino-neopentanol are added in the course of 15 minutes to a mixture of 1,220 parts of 37 per cent strength by weight formaldehyde and 290 parts of propionaldehyde whilst stirring at from 20 to 70°C. The reaction mixture is stirred for a further 30 minutes at from 75 to 80°C. The formaldehyde content is lowered to 0.05% by weight (based on the mixture) by stripping with steam and the water and low-boiling constituents are removed by distillation, using a Sambay evaporator at 125°C and 10 mm Hg. 504 parts of crude 2,2-dimethylolpropanal, corresponding to 85.4% of theory, based on propionaldehyde, are left as the residue. Distillation at 140—150°C and 1—2 mm Hg gives 484 parts of dimethylolpropanal of boiling point 125°C at 1—2 mm Hg, corresponding to 82% of theory, based on propionaldehyde. Hydrogenation of the dimethylolpropanal in methanol, analogously to Example 1, gives a solution of 465 parts of trimethylolethane. On distilling off the solvent, and recrystallizing the residue from diisopropyl ketone, 454 parts of trimethylolethane of melting point 196°C are obtained, corresponding to 75.6% of theory, based on propionaldehyde.

WHAT WE CLAIM IS:-

1. A process for the manufacture of an α,α -dimethylol-substituted aliphatic aldehyde of the formula

I

п

where R^1 is an aliphatic radical, by reaction of an aldehyde with formaldehyde in the presence of a base, wherein an aldehyde of the formula

20

25

30

35

5

where R¹ has the above meaning, is reacted with formaldehyde in the presence as catalyst of a tertiary amine base of the formula

where R² and R³ separately are identical or different aliphatic radicals or together form with the linking nitrogen a heterocyclic ring, and R⁴ and R⁵ are identical or different aliphatic radicals, and in addition (i) R⁴ may denote hydrogen if (a) R⁵

$$R^{\mathfrak{s}}$$
 H $R^{\mathfrak{s}}$ $R^{\mathfrak{s}}$ or (b) $R^{\mathfrak{s}}$ denotes $R^{\mathfrak{s}}$ $R^{\mathfrak{s}}$

and R2+R3+the linking N atom form a heterocyclic ring or R5 denotes

10 and simultaneously R2 denotes

and (ii) R^a may denote hydrogen if (a) R^2+R^3+ the linking N atom form a heterocyclic ring and R^a denotes an aliphatic radical or (b) R^a denotes an aliphatic radical and R^a denotes

$$\begin{array}{c|c}
\mathbf{H} \\
\mathbf{R}^{\mathbf{c}} & & \\
\end{array}$$

15

20

25

30

35

40

Re throughout denoting an aliphatic radical and individual radicals Re and individual radicals Re being identical or different.

A process as claimed in claim 1, wherein the reaction is carried out using from
 to 8 moles of formaldehyde per mole of starting material II.

3. A process as claimed in claim 1 or 2, wherein the reaction is carried out at from 15 to 120°C.

4. A process as claimed in claim 1 or 2, wherein the reaction is carried out at from 30 to 90°C.

5. A process as claimed in claim 1 or 2, wherein the reaction is carried out at from 40 to 85°C.

6. A process as claimed in any of claims 1 to 5, wherein the reaction is carried out with an aqueous formaldehyde solution of from 20 to 40 per cent strength by weight.

7. A process as claimed in any of claims 1 to 6, wherein the reaction is carried out with an organic, readily water-miscible solvent which is inert under the reaction conditions.

8. A process as claimed in any of claims 1 to 6, wherein the reaction is carried out with from 50 to 1,000% by weight, based on starting material II, of an organic, readily water-miscible solvents which is inert under the reaction conditions.

9. A process as claimed in any of claims 1 to 8, wherein, in the formula of starting material II, R¹ is linear alkyl of 1 to 6 carbon atoms optionally substituted by one or more alkyl or alkoxy groups of 1 to 3 carbon atoms.

or more alkyl or alkoxy groups of 1 to 3 carbon atoms.

10. A process as claimed in any of claims 1 to 9, wherein the reaction is carried out with from 0.03 to 0.15 mole of the catalyst III per mole of starting material II.

	11. A process as claimed in any of claims 1 to 9, wherein the reaction is carried out with from 0.05 to 0.1 mole of the catalyst III per mole of starting material II. 12. A process as claimed in any of claims 1 to 11, wherein the reaction is carried	
5	out in the presence as catalyst of a tertiary amine as defined in claim 1 in which any aliphatic radical III, where the alkyl of 1 to 7 carbon atoms optionally substituted	5
	by one or more dialkylamino groups and/or hydroxyl groups, the alkyl groups of any dialkylamino groups being identical or different and each being of 1 to 5 carbon atoms, and any heterocyclic ring formed by R ² and R ³ together with the linking nitrogen	
10	atom has 5 or 6 ring members, which may include a further nitrogen atom or an oxygen atom and may further be substituted by one or more alkyl or alkoxy groups, in	· 10
	each case of 1 to 3 carbon atoms, dialkylamino groups, in each case of 1 to 3 carbon atoms per alkyl, or hydroxyl groups.	
1.6	13. A process as claimed in any of claims 1 to 12, wherein the reaction is carried out in the presence as catalyst of dimethylamino-neopentanol, 3-dimethylamino-	
15	2-methyl-2-propyl-propanol, 2,2-dimethyl-N,N'-tetramethyl-1,3-propylenediamine, pyrrolidino-neopentanol, 1-dimethylamino-neopentane, 1-dimethylamino-2,2-dimethylolpropane, 1-dimethylamino-2,2-dimethylolbutane, methyl-diisobutylamine,	15
	ethyl-diisopropylamine, propyl-diisopropylamine, triisopropylamine, triisobutylamine, propyl-diisobutylamine, N-isopropyl-pyrrolidine, N-isobutyl-	
20	pyrrolidine, N-isopropyl-piperidine, N-isobutyl-piperidine, methyl-ethylamino-neo- pentanol, diethylamino-neopentanol, piperidino-neopentanol, 3-(methyl-ethylamino)-2- methyl-2-propyl-propanol, 3-pyrrolidino-2-methyl-2-propyl-propanol, 3-piperidino-2-	20
	methyl-2-propyl-propanol, 3-dimethylamino-2-ethyl-2-butyl-propanol, 1-pyrrolidino-	
25	2,2-dimethylolpropane, 1-(methylethylamino)-2,2-dimethylolpropane, 1,3-bis-[dimethylamino] neopentane, 1,3-bis-[dimethylamino]-2,2-dimethyl-propanol, methylethylamino-neopentane, ethyl-diisobutylamine, butyl-diisopropylamine, tertbutyl-diisopropylamine, N-isopropylmorpholine, N,N'-diisopropyl-piperazine, N-isobutyl-morpholine, N,N'-diisobutyl-piperazine, N-tertbutyl-piper-	25
30	idine or N-tertbutyl morpholine. 14. A process for the manufacture of an ax-dimethylol-substituted aldehyde	30
	carried out substantially as described in any of the foregoing Examples 1 and 4 to 6. 15. \(\alpha \to \)Dimethylol-substituted aliphatic aldehydes when obtained by the process claimed in any of the claims 1 to 14.	30
35	16. Trimethylol compounds of the formula R ¹ —C(CH ₂ OH) ₃ where R ¹ has the	
33	meaning given in claim 1 or 9, when obtained from $\alpha_5\alpha$ -dimethylol-substituted aliphatic aldehydes as claimed in claim 15 by hydrogenation. 17. Polyurethane resins, alkyd resins, drying oil and plasticisers containing tri-	35
	methylolalkanes as claimed in claim 16. 18. Dimethylolarboxylic acids when obtained from α ₃ α-dimethylol-substituted	
40	aliphatic aldehydes claimed in claim 15.	40

J. Y. & G. W. JOHNSON,
Furnival House,
14—18 High Holborn,
London WC1V 6DE,
Chartered Patent Agents,
Agents for the Applicants.

Printed for Her Majesty's Stationery Office, by the Courier Press, Learnington Spa, 1978 Published by The Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.